














Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd Tel:+381 11 3103-999, fax. +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg

CENOVNIK OPREME VIDEO NADZOR 22-09-

R. Br.	Slika	Model	Opis	Cena (EUR)
DVR-ovi (NORA REALVIEW PRO - ANDROID, LONGSE TMEYE)				
1		HB7104X3-LH	HB7104X3-LH 4-kanalni DVR, snimanje sva 4 kanala u 960H rezoluciji.1 SATA HD (nije uključen). Playback 4 kanala simultano. Mini 1H kućište, 2 audio ulaza/1 izlaz; 4 alarmna ulaza/1 izlaz; 4 zone za maskiranje; Izlazi: HDMI, VGA, CVBS; napajanje 12V DC/24W; P2P, Anroid/Iphone besplatan softver za daljinski pristup. Cloud servis za povezivanje sa uređajem preko Interneta jednostavnim skeniranjem QR koda pomoću kamere na mobilnom telefonu.	61,46 €
2		LS - 9604PD	LS - 9604PD Video Input/Output: BNC 4CH In/ 1CH Out/ VGA 1CH Out Audio Input/Output: RCA 2CH In/ 1CH Out Compression Method: H.264 Real time recording support: CIF: 352x240 with 120 Fps (NTSC); 352x288 with 100 Fps (PAL) D1: 720x480 with 120 Fps (NTSC); 704x576 with 100 Fps (PAL) 960H: 960x480 with 120 Fps (NTSC); 960x576 with 100 Fps (PAL) Preview resolution: 960 x 480 (NTSC), 960 x 576 (PAL); Playback resolution: 960H x 4 Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback 1 RJ - 45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software 2xUSB 1 SATA Hard Disk interface (2.5/3.5" SATA,Up to 4TB) Backup: USB2.0 and Network Support remote view by Mobilephone 960H*4CH, Network Standard Color: White Optional Color: Black (Model LS - 9604PDB) VGA, USB Backup, USB Mouse Dimensions (LxWxH): 215*215*53(mm) weight: 2kg	66,99 €
3		HB7108X3-LH	HB7108X3-LH 8-kanalni DVR, snimanje svih 8 kanala u 960H rezoluciji.1 SATA HD (nije uključen). Playback 8 kanala simultano. Mini 1H kućište, 2 audio ulaza/1 izlaz; 4 alarmna ulaza/1 izlaz; 4 zone za maskiranje; Izlazi: HDMI, VGA, CVBS; napajanje 12V DC/24W; P2P, Anroid/Iphone besplatan softver za daljinski pristup	100,80 €
4		HB7016X3-HAT	HB7016X3-HAT DVR 16 kanala. 1 SATA HD (nije uključen)16 ch snimanje 2 kanala u 960H rezoluciji i 14 kanala u CIF ili 16 kanala u 960H rezoluciji pri 100/120fps ili 960H@137.5/165fps 4kanala simultani playback mini 1U kućište audio 1 ulaz/ 1 izlaz 4 zone maskiranja Izlazi: HDMI , VGA Napajanje: DC12V, 24W. Anroid/Iphone besplatan softver za daljinski pristup	131,60 €
5		HB7216X3	HB7216X3 16-kanalni DVR, snimanje svih 16 kanala u 960H rezoluciji.2 SATA HD-a (nisu uključeni). Playback 16 kanala simultano u 960H rezoluciji. Mini 1,5U kućište, 2 audio ulaza/1 izlaz; 4 alarmna ulaza/1 izlaz; 4 zone za maskiranje; Izlazi: HDMI, VGA, CVBS, SPOT; napajanje 12V DC/40W; P2P, Anroid/Iphone besplatan softver za daljinski pristup	253,40 €
6		HB7232X3	HB7232X3 32-kanalni DVR, snimanje svih 32 kanala u 960H rezoluciji.4 SATA HD-a (nisu uključeni). Playback 16 kanala simultano u 960H rezoluciji. Mini 1,5U kućište, 4 audio ulaza/1 izlaz; 4 alarmna ulaza/1 izlaz; 4 zone za maskiranje; Izlazi: HDMI, VGA, CVBS, SPOT; napajanje 12V DC/90W; P2P, Anroid/Iphone besplatan softver za daljinski pristup	623,00 €
7		LS - 9604U	LS - 9604U Video Input/Output: BNC 4CH In/ 1CH Out/ VGA 1CH Out, HDMI 1CH Out Audio Input/Output: RCA 4CH In/ 1CH Out Compression Method: H.264 Real time recording support: CIF: 352x240 with 120 Fps (NTSC); 352x288 with 100 Fps (PAL) D1: 720x480 with 120 Fps (NTSC); 704x576 with 100 Fps (PAL) 960H: 960x480 with 120 Fps (NTSC); 960x576 with 100 Fps (PAL) Preview resolution: 960 x 480 (NTSC), 960 x 576 (PAL); Playback resolution: 960H x 4 Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback 1 RJ - 45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software PTZ, RS485 x 1, 2 x USB, 1 x IR Controller 1 SATA Hard Disk interface (Up to 4TB) Backup: USB2.0 and Network 960H*4CH, RS485, PTZ, Network Support remote view by Mobilephone HDMI,VGA, USB Backup, USB Mouse Dimenzije (LxWxH): 354x245mmx45mm, težina: 4.0kg	96,60 €








Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd
Tel: +381 11 3103-999, fax. +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg

CENOVNIK OPREME VIDEO NADZOR 22-09-

R. Br.	Slika	Model	Opis	Cena (EUR)
8		LS-2008PD (LS-9608K)	LS-2008PD Video Input/Output: BNC 8CH In/ 1CH Out, VGA 1CH Out Audio Input/Output: RCA 2CH In/ 1CH Out Compression Method: H.264 Real time recording support: CIF:352x240 with 240 Fps (NTSC); 352x288 with 200 Fps (PAL) D1:720x480 with 240 Fps (NTSC); 704x576 with 200 Fps (PAL) 960H:960x480 with 240 Fps (NTSC); 960x576 with 200 Fps (PAL) Preview resolution: 960 x 480 (NTSC), 960 x 576 (PAL) ; Playback resolution: 960H x 4 Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback 1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software 2 x USB 1 SATA Hard Disk interface (2.5/3.5' SATA, Up to 4TB) Backup: USB2.0 and Network Support remote view by Mobilephone Standard Color: White Optional Color: Black (Model LS-2008PDB) Dimensions (LxWxH): 215*215*53(mm) težina: 2kg	95,48 €
9		LS-9604H	LS-9604H Video Input/Output: BNC 4CH In/ 1CH Out/ VGA 1CH Out, HDMI 1CH Out Audio Input/Output: RCA 4CH In/ 1CH Out Compression Method: H.264 Real time recording support: CIF: 352x240 with 120 Fps (NTSC); 352x288 with 100 Fps (PAL) D1: 720x480 with 120 Fps (NTSC); 704x576 with 100 Fps (PAL) 960H: 960x480 with 120 Fps (NTSC); 960x576 with 100 Fps (PAL) Preview resolution: 960 x 480 (NTSC), 960 x 576 (PAL) ; Playback resolution: 960H x 4 Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback 1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software PTZ, RS485 x 1, 2 x USB, 1 x IR Controller 1 SATA Hard Disk interface (Up to 4TB) Backup: USB2.0 and Network Support remote view by Mobilephone Dimenzije (LxWxH): 280x240mmx43mm, težina: 3.5kg	84,70 €
10		LS-9608U	LS-9608U Video Input/Output: BNC 8CH In/ 1CH Out, VGA 1CH Out, HDMI 1CH Out Audio Input/Output: RCA 4CH In/ 1CH Out Alarm Input/Output: Alarm 4CH In/ 1CH Out Compression Method: H.264 Real time recording support: CIF:352x240 with 240 Fps (NTSC); 352x288 with 200 Fps (PAL) D1:720x480 with 240 Fps (NTSC); 704x576 with 200 Fps (PAL) 960H:960x480 with 240 Fps (NTSC); 960x576 with 200 Fps (PAL) Preview resolution: 720 x 480 (NTSC), 704 x 576 (PAL) ; Playback resolution: 960H x 4 Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback 1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software PTZ, RS485 x 1, 2 x USB, 1 x IR Controller 1 SATA Hard Disk interface (Up to 4TB) Backup: USB2.0 and Network Support remote view by Mobilephone Dimenzije (LxWxH): 354x245mmx45mm, težina: 4.0kg	130,90 €
11		LS-9616K (LS-9608U)	Video Input/Output: BNC 16CH In / 1CH Out, VGA 1CH Out, HDMI 1CH Out Audio Input/Output: RCA 4CH In/ 1CH Out Alarm Input/Output: Alarm 4CH In/ 1CH Out Compression Method: H.264 Real time recording support: CIF:352x240 with 480 Fps (NTSC); 352x288 with 400 Fps (PAL) D1:720x480 with 480 Fps (NTSC); 704x576 with 400 Fps (PAL) 960H: 960x480 with 480 Fps (NTSC); 960x576 with 400 Fps (PAL) Preview resolution: 960 x 480 (NTSC), 960x 576 (PAL) ; Playback resolution: 960H x 4 Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback 1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS, Support Internet Explorer and special client software PTZ, RS485x1, 2xUSB, 1xIR Controller 2 SATA Hard Disk interface (Up to 8TB) Backup: USB2.0 and Network Support remote view by Mobilephone Dimensions (LxWxH): 354x245mmx45mm, težina: 4.0kg	200,20 €
12		LS-3116E	LS-3116E Video Input/Output: BNC 16CH In / 1CH Out, VGA 1CH Out, HDMI 1CH Out Audio Input/Output: RCA 16CH In/ 1CH Out Alarm Input/Output: Alarm 4CH In/ 1CH Out Compression Method: H.264 Real time recording support: CIF:352x240 with 480 Fps (NTSC); 352x288 with 400 Fps (PAL) D1:720x480 with 480 Fps (NTSC); 704x576 with 400 Fps (PAL) 960H: 960x480 with 480 Fps (NTSC); 960x576 with 400 Fps (PAL) Preview resolution: 960 x 480 (NTSC), 960x 576 (PAL) ; Playback resolution: 960H x 4 Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback 1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS, Support Internet Explorer and special client software Remote Control, PTZ, RS485, Alarm, 2xUSB, 1xIR Controller 2 SATA Hard Disk interface (Up to 8TB) Backup: USB2.0 and Network Support remote view by Mobilephone Dimenzije (LxWxH): 405mmx330mmx65mm, težina: 6.0kg	207,90 €
13		LS-9304U	LS-9304U DVR 4 KANALA SNIMANJE I PRIKAZ SVIH KANALA U D1 REZOLUCIJI D1*4CH, RS485, PTZ, Network VGA, USB Backup, USB Mouse Video Input/Output: BNC 4CH In/ 1CH Out / VGA 1CH Out Audio Input/Output: RCA 1CH In/ 1CH Out Compression Method: H.264 Real time recording support: CIF:352x240 with 120 Fps (NTSC); 352x288 with 100 Fps (PAL) D1:720x480 with 120 Fps (NTSC); 704x576 with 100 Fps (PAL) Preview resolution: 720 x 480 (NTSC), 704 x 576 (PAL) ; Playback resolution: D1 x 4 Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback 1 RJ - 45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software Remote Control, PTZ, RS485 x 1, 2 x USB, 1 x IR Controller 1 SATA Hard Disk interface Backup: USB2.0 and Network D1*4CH, RS485, PTZ, Network Support remote view by Mobilephone VGA, USB Backup, USB Mouse Dimensions (LxWxH): 355x230mmx45mm, weight: 4.0kg	76,85 €








Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd
Tel: +381 11 3103-999, fax. +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg

CENOVNIK OPREME VIDEO NADZOR 22-09-

R. Br.	Slika	Model	Opis	Cena (EUR)
14		LS - 9508PD (LS-9604PK)	LS - 9508PD Video Input/Output: BNC 8CH In/ 1CH Out, VGA 1CH Out Audio Input/Output: RCA 2CH In/ 1CH Out Compression Method: H.264 Real time recording support: CIF:352x240 with 240 Fps (NTSC); 352x288 with 200 Fps (PAL) D1:720x480 with 240 Fps (NTSC); 704x576 with 200 Fps (PAL) Preview resolution: 720 x 480 (NTSC), 704 x 576 (PAL); Playback resolution: D1 x 4 Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback 1 RJ - 45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software 2 x USB 1 SATA Hard Disk interface (2.5/3.5' SATA, Up to 4TB) Backup: USB2.0 and Network Support remote view by Mobilephone D1*8CH, Network Standard Color: White Optional Color: Black (Model LS - 9508PDB) VGA, USB Backup, USB Mouse Dimenzije (LxWxH): 215*215*53(mm) težina: 2kg	90,48 €
15		LS - 9308U	LS - 9308U DVR 8 KANALA *Video Input/Output: BNC 8CH In/ 1CH Out/ VGA 1CH Out *Audio Input/Output: RCA 1CH In/ 1CH Out *Compression Method: H.264 *Real time recording support: *CIF:352x240 with 240 Fps (NTSC); 352x288 with 200 Fps (PAL) *D1:720x480 with 60 Fps (NTSC); 704x576 with 50 Fps (PAL) *Preview resolution: 720 x 480 (NTSC), 704 x 576 (PAL); *Playback *resolution: CIF x 8 / D1 x 1 *Hexaplex operation simultaneously: Preview, recording, playback, and *network live, backup, playback *1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support *Internet Explorer and special client software *Remote Control, PTZ, RS485 x 1, 2 x USB, 1 x IR Controller *1 SATA Hard Disk interface *Backup: USB2.0 and Network *Support remote view by Mobilephone *Dimenzije (LxWxH): 355x230mmx45mm, težina: 4.0kg	106,26 €
16		LS-9316U	LS-9316U DVR 16 KANALA CIF*16CH, RS485, PTZ, Network VGA, USB Backup, USB Mouse Video Input/Output: BNC 16CH In / 1CH Out, VGA 1CH Out, Audio Input/Output: RCA 2CH In/ 1CH Out Compression Method: H.264 Real time recording support: CIF:352x240 with 480 Fps (NTSC); 352x288 with 400 Fps (PAL) Preview resolution: 720 x 480 (NTSC), 704 x 576 (PAL); Playback resolution: CIF x 4 Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback 1 RJ - 45 Ethernet connector, Static, Dynamic IP and DDNS, Support Internet Explorer and special client software Remote Control, PTZ, RS485x1, 2xUSB, 1xIR Controller 1 SATA Hard Disk interface Backup: USB2.0 and Network CIF*16CH, RS485, PTZ, Network Support remote view by Mobilephone VGA, USB Backup, USB Mouse Dimenzije (LxWxH): 355x230mmx45mm, težina: 4.0kg	146,30 €
17		LS-9616E	LS-9616E DVR 16 KANALA D1*16CH, RS485, PTZ, Alarm, Network 2 SATA HD, HDMI, VGA, USB Backup, USB Mouse Video Input/Output: BNC 16CH In / 2CH Out, VGA 1CH Out, HDMI 1CH Out, ESATA Out Audio Input/Output: RCA 8CH In/ 1CH Out Alarm Input/Output: Alarm 16CH In/ 2CH Out Compression Method: H.264 Real time recording support: CIF:352x240 with 480 Fps (NTSC); 352x288 with 400 Fps (PAL) D1:720x480 with 480 Fps (NTSC); 704x576 with 400 Fps (PAL) Preview resolution: 720 x 480 (NTSC), 704 x 576 (PAL); Playback resolution: D1 x 8 Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback 1 RJ - 45 Ethernet connector, Static, Dynamic IP and DDNS, Support Internet Explorer and special client software Remote Control, PTZ, RS485x2, 2xUSB, 1xIR Controller 2SATA Hard Disk interface Backup: USB2.0 and Network D1*16CH, RS485, PTZ, Alarm, Network Support remote view by Mobilephone 2 SATA HD, HDMI, VGA, USB Backup, USB Mouse	304,92 €
AHDVR-ovi				
18		HB-DVR5104-BH	HB-DVR5104-BH 4-kanalni AHDVR 1 SATA HD (nije uključen) Hi3520D čip snimanje 4 kanala u 960H rezoluciji pri 25fps; Playback 4 kanala u 720P rezoluciji pri 25fps, Audio 2 ulaza/1 izlaz; 4 alarmna ulaza/1 izlaz 4 zone maskiranja; Izlazi: HDMI , VGA; Napajanje DC 12V/40W. Anroid/Iphone besplatan softver za daljinski pristup	110,60 €
19		HB-DVR5108-BH	HB-DVR5108-BH 8-kanalni AHDVR 1 SATA HD (nije uključen) Hi3521 čip snimanje 8*720P@15fps or 6*720@25fps or 8*960H@25fps; Playback 8*720P@15fps ili 6*720@25fps, Audio 2 ulaza/1 izlaz; 4 alarmna ulaza/1 izlaz 4 zone maskiranja; Izlazi: HDMI , VGA; Napajanje DC 12V/40W. Anroid/Iphone besplatan softver za daljinski pristup	165,20 €
NVR-ovi (NORA REALVIEW PRO - ANDROID)				
20		HB-NVR2104T	HB-NVR2104T 4-KANALNI NVR 1 SATA HD (nije uključen) Hi3520D čip Snimanje 4 kanala u 1080P rezoluciji pri 20Mbps, 4*960P/1*1080P realtime mini 1U kućište, 4 audio ulaza/0 izlaza; Izlazi: HDMI , VGA. Napajanje 12V DC/24W Anroid/Iphone besplatan softver za daljinski pristup	96,60 €

Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd
Tel: +381 11 3103-999, fax. +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg

CENOVNIK OPREME VIDEO NADZOR 22-09-

R. Br.	Slika	Model	Opis	Cena (EUR)
21	 NORA	HB-NVR2108T	HB-NVR2108T 8-KANALNI NVR 1 SATA HD (nije uključen) Hi3520D čip Snimanje 8 kanala u 1080P rezoluciji pri 40Mbps; 4ch u 960P rezoluciji ili 1ch*1080P realtime mini 1U kućište 8 audio ulaza/8 izlaza; Izlazi: HDMI , VGA Napajanje 12V DC/24W Anroid/Iphone besplatan softver za daljinski pristup	113,40 €
22	 NORA	HB-NVR2208E	HB-NVR2208E 8 kanalni NVR; 2 SATA HD-a (nisu uključeni) Hi3535 čip Snimanje 8 kanala u 1080P rezoluciji pri 40Mbps Playback 8 kanala u 1080P rezoluciji Audio 8 ulaza sa IP kamera + 1RCA ulaz/1 RCA izlaz 4 alarmna ulaza/2 alarmna izlaza Izlazi: HDMI , VGA Napajanje: DC12V, 90W; Anroid/Iphone besplatan softver za daljinski pristup	198,80 €
23	 NORA	HB-NVR2216E	HB-NVR2216E 16 kanalni NVR; 2 SATA HD-a (nisu uključeni) Hi3535 čip Snimanje 16 kanala u 1080P rezoluciji pri 80Mbps Playback 16 kanala u 1080P rezoluciji kućište 1,5U Audio 16 ulaza sa IP kamera + 1RCA ulaz/1 RCA izlaz 4 alarmna ulaza/2 alarmna izlaza Izlazi: HDMI , VGA Napajanje: DC12V, 90W; Anroid/Iphone besplatan softver za daljinski pristup	263,20 €
24	 NORA	HB-NVR2432	HB-NVR2432 32 kanalni NVR; 4 SATA HD-a (nisu uključeni) Hi3535 čip Snimanje 32 kanala u 1080P rezoluciji pri 160Mbps Playback 8 kanala u 1080P rezoluciji kućište 1,5U Audio 32 ulaza sa IP kamera + 1RCA ulaz/1 RCA izlaz 4 alarmna ulaza/2 alarmna izlaza Izlazi: HDMI , VGA Napajanje: DC12V, 90W 1GB mrežni port Anroid/Iphone besplatan softver za daljinski pristup	441,00 €
25	 longse	LS - N2008PD (LS-9208H)	LS - N2008PD 8-kanalni NVR IP kamera Input: 8CH (1920x1080, 1280x960, 1280x720, etc) Video Output: 1CH VGA Output, 1CH HDMI Output Compression Method: H.264 Recording Resolution: 8CHx1080P/8CHx960P/8CHx720P, etc Preview Resolution: 8CHxD1 /1CHx1080P Playback Resolution: 1CHx1080P Hexaplex Operation Simultaneously: Preview, Recording, Playback, Live, Backup 1 RJ - 45 Ethernet Connector, Static IP , Support IE and Special CMS 1 SATA Hard Disk Interface (2.5/3.5' SATA, Up to 4TB) Backup: 2xUSB2.0 Support Remote View by Smart Phone Standard Color: White Optional Color: Black (Model LS - N2008PDB) Dimenzije (LxWxH): 215*215*53(mm) težina: 2kg	92,40 €
26	 longse	LS - N3116E	LS - N3116E 16-kanalni NVR IP kamera Input: 16CH (1920x1080, 1280x960, 1280x720, etc) Video Output: 1CH VGA Output, 1CH HDMI Output Compression Method: H.264 Recording Resolution: 16CHx1080P/16CHx960P/16CHx720P, etc Preview Resolution: 16CHxD1/9CHxD1/1CHx1080P Playback resolution: 4CHx1080P Hexaplex Operation Simultaneously: Preview, Recording, Playback, Live, Backup 1 RJ - 45 Ethernet Connector, Static IP , Support IE and Special CMS 2 SATA Hard Disk interface (Up to 8TB) Backup: 2xUSB2.0 Support Remote View by Smart Phone Dimenzije (LxWxH): 405*325*65(mm) težina: 6kg	215,60 €
27	 longse	LS - N3524E	LS - N3524E NVR 24 kanala IP kamera Input: 24CH (1920x1080, 1280x960, 1280x720, etc) Video Output: 1CH VGA Output, 1CH HDMI Output Compression Method: H.264 Recording Resolution: 24CHx1080P/24CHx960P/24CHx720P, etc (All Real Time) Preview Resolution: 24CHxD1/16CHxD1/9CHxD1/4CHxD1/1CHx1080P Playback resolution: 4CHx1080P Hexaplex Operation Simultaneously: Preview, Recording, Playback, Live, Backup 1 RJ - 45 Ethernet Connector, Static IP, P2P, Support IE and Special CMS 2 SATA Hard Disk interface (Up to 8TB) Backup: 2xUSB2.0 Support Remote View by Smart Phone Dimensions (LxWxH): 405*325*65(mm) težina: 6kg	231,00 €









Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd
Tel:+381 11 3103-999, fax. +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg

CENOVNIK OPREME VIDEO NADZOR 22-09-

R. Br.	Slika	Model	Opis	Cena (EUR)
TRIBRIDNI HD-CVR snimači (HDCVI MMS android)				
28		NCR-4104XD	<p>NCR-4104XD 4-kanalni Tribriid: HDCVI/Analog/IP Adaptive 4CH. Network, 1 x SATA, P2P HDMI, VGA, USB Backup, USB Mouse; Video Input: CVI: 4CHx720P / IPC: Max 2CHx1080P / Analog: 4CHx960H/4CHxD1 Video Output: VGA 1CH Out/ HDMI 1CH Out Audio Input/Output: RCA 1CH In/ 1CH Out Compression Method: H.264 HDCVI: 720P, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; Analog: 960H/D1, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; IPC: 1080P/960P/720P, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; Preview resolution: 720P (1280*720) /1080P (1920*1080) Single/Multi-channel playback: 1/4CHx720P@30fps Hexaplex operation simultaneously: Live, Recording, Playback, Network Operating Static, Dynamic IP and DDNS , P2P, Support IE and special client software 1 SATA Hard Disk Interface (Up to 4TB); 2xUSB (1 Rear) ; 1xRJ45; Backup: USB2.0 (such as U disk, mobile hard disk, USB Drive) and network Tribriid: HDCVI/Analog/IP Adaptive Support remote view by Mobilephone (iPhone, iPad, Android, Windows Phone) 4CH, NDC12V ≤15W (With adaptor, without hard disk) HDMI, VGA, USB Backup, USB Mouse Dimensions (LxWxH): 258*232*42(mm) Weight: 2.2kg</p>	68,60 €
29		NCR-4108XD	<p>NCR-4108XD 8-kanalni HD-CVR snimač Video Input/Output: BNC 8CH In/ 1CH Out/ VGA 1CH Out/ HDMI 1CH Out Audio Input/Output: RCA 1CH In/ 1CH Out Compression Method: H.264 720P/960P, real-time mode: PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; 1080P, non real-time mode: PAL every channel 1fps-12fps adjustable; NTSC every channel 1fps-15fps adjustable Preview resolution: 720P(1280*720) /1080P(1920*1080) Multi-channel playback: Support single channel/four channels mode. Hexaplex operation simultaneously: Live, Recording, Playback, Network Operating Static, Dynamic IP and DDNS , P2P, Support Internet Explorer and special client software 2xUSB (1 Rear) ; 1xRJ45 2 SATA Hard Disk interface (Up to 8TB) Backup: USB2.0 (such as U disk, mobile hard disk, USB drive) and Network Support remote view by Mobilephone(iPhone, iPad, Android, Windows Phone) 8CH, Network, P2P DC 12V ≤15W(with adaptor, without hard disk) HDMI, VGA, USB Backup, USB Mouse Dimensions (LxWxH): 335*270*55(mm) Weight: 2.5kg</p>	105,00 €
30		NCR-4216D	<p>NCR-4216D Video Input: CVI: 16CHx720P / IPC: Max 4CHx1080P / Analog : 16CHx960H/16CHxD1 Video Output: VGA 1CH Out/ HDMI 1CH Out Audio Input/Output: RCA 1CH In/ 1CH Out Compression Method: H.264 HDCVI: 720P, PAL every channel 1fps-12fps adjustable; NTSC every channel 1fps-15fps adjustable Analog: 960H/D1, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; IPC: 1080P/960P/720P, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; Preview resolution: 720P (1280*720) /1080P(1920*1080) Single/Multi-channel playback: 1/4/9/16CHx720P@15fps Hexaplex operation simultaneously: Live, Recording, Playback, Network Operating Static, Dynamic IP and DDNS , P2P, Support IE and special client software 2 SATA Hard Disk Interface (Up to 8TB); 2xUSB (1 Rear) ; 1xRJ45; Tribriid: HDCVI/Analog/IP Adaptive Backup: USB2.0 (such as U disk, mobile hard disk, USB Drive) and network 16CH, Network, 2 x SATA, P2P Support remote view by Mobilephone (iPhone, iPad, Android, Windows Phone) HDMI, DC12V ≤15W (With adaptor, without hard disk) Dimensions (LxWxH): 335*270*55(mm) Weight: 2.5kg 720P</p>	217,00 €















Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd
Tel: +381 11 3103-999, fax. +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg

CENOVNIK OPREME VIDEO NADZOR 22-09-

R. Br.	Slika	Model	Opis	Cena (EUR)
TRIBRIDNI FULL HD-CVR snimači (HDCVI MMS)				
31		NCR-5104D	NCR-5104D tribridni FULL HD snimač 4 kanala Video Input: CVI: 4CHx1080P / IPC: Max 2CHx1080P / Analog: 4CHx960H/4CHxD1 Video Output: VGA 1CH Out/ HDMI 1CH Out Audio Input/Output: RCA 1CH In/ 1CH Out Compression Method: H.264 HDCVI: 1080P, PAL every channel 1fps-12fps adjustable; NTSC every channel 1fps-15fps adjustable HDCVI: 720P, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; Analog: 960H/D1, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; IPC: 1080P/960P/720P, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; Preview resolution: 720P (1280*720) /1080P(1920*1080) Single/Multi-channel playback: 1/4CHx720P@30fps, 1/4CHx1080P@15fps Hexaplex operation simultaneously: Live, Recording, Playback, Network Operating Static, Dynamic IP and DDNS, P2P, Support IE and special client software 1 SATA Hard Disk Interface (Up to 4TB); 2xUSB (1 Rear); 1xRJ45; Backup: USB2.0 (such as U disk, mobile hard disk, USB Drive) and network Tribrid: 2CH HDCVI Support remote view by Mobilephone (iPhone, iPad, Android, Windows Phone) 4CH, Network, DC12V ≤15W(With adaptor, without hard disk) HDMI, VGA, USB Backup, USB Mouse Dimensions (LxWxH): 335*270*55(mm) Weight: 2.5kg 1080P	92,40 €
32		NCR-5208D	NCR-5208D Video Input: CVI: 8CHx1080P / IPC: Max 4CHx1080P / Analog: 8CHx960H/8CHxD1 Video Output: VGA 1CH Out/ HDMI 1CH Out Audio Input/Output: RCA 1CH In/ 1CH Out Compression Method: H.264 HDCVI: 1080P, PAL every channel 1fps-12fps adjustable; NTSC every channel 1fps-15fps adjustable; HDCVI: 720P, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; Analog: 960H/D1, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; IPC: 1080P/960P/720P, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; Preview resolution: 720P (1280*720) /1080P (1920*1080) Single/Multi-channel playback: 1/4/8CHx720P@30fps, 1/4/8CHx1080P@15fps Hexaplex operation simultaneously: Live, Recording, Playback, Network Operating Static, Dynamic IP and DDNS, P2P, Support IE and special client software 2 SATA Hard Disk interface (Up to 8TB); 2xUSB (1 Rear); 1xRJ45 Backup: USB2.0 (such as U disk, mobile hard disk, USB drive) and Network Tribrid: 4CH HDCVI & 4CH IP Support remote view by Mobilephone (iPhone, iPad, Android, Windows Phone) Dimensions (LxWxH): 335*270*55(mm) Weight: 2.5kg	154,00 €
33		NCR-5216D	NCR-5216D Video Input: CVI: 16CHx1080P / IPC: Max 4CHx1080P / Analog: 16CHx960H/16CHxD1 Video Output: VGA 1CH Out/ HDMI 1CH Out Audio Input/Output: RCA 1CH In/ 1CH Out Compression Method: H.264 HDCVI: 1080P, PAL every channel 1fps-12fps adjustable; NTSC every channel 1fps-15fps adjustable; HDCVI: 720P, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; Analog: 960H/D1, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; IPC: 1080P/960P/720P, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; Preview resolution: 720P (1280*720) /1080P (1920*1080) Single/Multi-channel playback: 1/4/9/16CHx720P@30fps, 1/4/9/16CHx1080P@15fps Hexaplex operation simultaneously: Live, Recording, Playback, Network Operating Static, Dynamic IP and DDNS, P2P, Support IE and special client software 2 SATA Hard Disk interface (Up to 8TB); 2xUSB (1 Rear); 1xRJ45 Tribrid: 12CH HD-CVI & 4CH IP Backup: USB2.0 (such as U disk, mobile hard disk, USB drive) and Network 16CH, Network, 2 x SATA, P2P Support remote view by Mobilephone (iPhone, iPad, Android, Windows Phone)	303,80 €
HD-CVI kamere 1 MPIX				
34		NORA NCR-10FDP	NC-10FDP 1/4" OV 1.0MP CMOS Sensor, 720P, With IR-CUT, DNR, Plastic IR Dome Camera IR LED: 14μ x 18PCS IR range: 20M Board Lens 3.6mm/F2.0 Size: 90.5(W) x 80(H) x 80(D)mm Weight: 300g	22,40 €
35		NCR-10FBP	NC-10FBP 1/4" OV 1.0MP CMOS senzor, 720P, sa IR-CUT, DNR, plastična Weatherproof IR kamera IR LED diode: 14μ x 18PCS Domet IR dioda: 20M Board Len 2.8mm/F2.0 stepen zaštite: IP66 Noslač sa 3-ose rotacije i zaštitom od sečenja kabla Dimenzije: 160.8(W) x 62(H) x 62(D)mm Težina: 380g	22,40 €
36		NCR-10FBM	NC-10FBM 1/4" OV 1.0MP CMOS senzor, 720P, sa IR-CUT, DNR, IR LED diode: 14μ x 20PCS Domet IR dioda: 25M Board Len 3.6mm/F2.0 stepen zaštite: IP66 Noslač sa 3-ose rotacije i zaštitom od sečenja kabla Dimenzije: 155.5(W) x 66(H) x 67(D)mm Težina: 750g	23,80 €













Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd
Tel: +381 11 3103-999, fax. +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg

CENOVNIK OPREME VIDEO NADZOR 22-09-

R. Br.	Slika	Model	Opis	Cena (EUR)
37		NC-10FDM	NC-10FDM 1/4" OV 1.0MP CMOS senzor, 720P, sa IR-CUT, DNR , antivandal IR Dome kamera Nove IR LED diode: 14µ x 18PCS IR LED diode: € 5 (12µ) x 24PCS (Optional) Domet IR dioda: 20M Optika na ploči 2.8mm/F2.0 Dimenzije: € 89 x 76(H) mm Težina: 450g	28,00 €
38		NC-10FD2	NC-10FD2 1/4" OV 1.0MP CMOS senzor, 720P, sa IR-CUT, DNR , antivandal IR Dome kamera IR LED diode: 18.5µ x 2PCS Domet IR dioda: 20M Optika na ploči 2.8mm/F2.0 Dimenzije: € 120 x 100(H) mm Težina: 800g	43,40 €
39		NC-10FB7	NC-10FB7 1/4" OV 1.0MP CMOS senzor, 720P, sa IR-CUT, DNR , IR LED diode: 42µ x 4PCS Domet IR dioda: 60M Optika na ploči 4mm/F2.0 stepen zaštite: IP66 Dimenzije: 194(W) x 91(H) x 82(D)mm Težina: 668g sa nosačem	36,40 €
40		NC-10FB8	NC-10FB8 1/4" OV 1.0MP CMOS senzor, 720P, sa IR-CUT, DNR , IR LED diode: 42µ x 2PCS Domet IR dioda: 60M Optika na ploči 4mm/F2.5 stepen zaštite: IP66 Dimenzije: 167(W) x 87(H) x 97(D)mm Težina: 1.2kgs sa nosačem	49,00 €
41		NC-10FB9	NC-10FB9 1/4" OV 1.0MP CMOS senzor, 720P, sa IR-CUT, DNR , IR LED diode: 42µ x 4PCS Domet IR dioda: 90M Optika na ploči 4mm/F2.5 stepen zaštite: IP66 Dimenzije: 205(W) x 88(H) x 120(D)mm Težina: 1.3kgs sa nosačem	55,30 €
42		NC-10FD	NC-10FD HD-CVI BULLET kamera 1/4" Aptina 1.0MP CMOS Sensor, 720P/960H, With IR-CUT, Low Illumination, DNR Bullet IR Camera IR LED: € 5 (12µ) x 24PCS IR range: 20M Board Lens 3.6mm/F2.0 Size: € 89 x 76(H) mm Weight: 450g	25,20 €
43		NC-10FB	NC-10FB HD-CVI bullet kamera 1/4" Aptina 1.0MP CMOS Sensor, 720P/960H, With IR-CUT, Low Illumination, DNR IR LED: € 5 (12µ) x 24PCS IR range: 20M Board Len 3.6mm/F2.0 Water resistance: IP66 Anti-Cut 3-Axis Bracket Size: 157(W) x 70(H) x 66(D)mm Weight: 650g	26,60 €
44		NC-10FB1	NC-10FB1 HD-CVI bullet kamera 1/4" Aptina 1.0MP CMOS Sensor, 720P/960H, With IR-CUT, Low Illumination, DNR IR LED: 42µ x 1PCS IR range: 20M Board Lens 3.6mm/F2.0 Water Resistance: IP66 Dimenzije: 130(W) x 77.5(H) x 80(D)mm Težina: 800g	35,00 €
45		NC-10VFD	NC-10VFD HD-CVI vandal dome kamera 1/4" Aptina 1.0MP CMOS Sensor, 720P/960H, With IR-CUT, Low Illumination, DNR Vandalproof IR Dome Kamera IR LED: € 5 (12µ) x 36PCS IR range: 30M 2.8-12mm Manual Zoom Optika Dimenzije: 125(W) x 105.8(H) x 135(D) mm Težina: 800g	35,00 €
46		NC-10VFB4	NC-10VFB4 HD-CVI bullet kamera 1/4" OV 1.0MP CMOS Sensor, 720P, With IR-CUT, DNR NEW IR LED: 14µ x 30PCS IR range: 40M 2.8-12mm Manual Zoom Optika Water resistance: IP66 Anti-Cut 3-Axis Bracket Dimenzije: 260(W) x 112(H) x 85(D)mm Težina: 1.4Kg	49,00 €
47		NC-10VFB6	NC-10VFB6 HD-CVI bullet kamera 1/4" OV 1.0MP CMOS Sensor, 720P, With IR-CUT, DNR NEW IR LED: 14µ x 48PCS IR range: 60M 2.8-12mm Manual Zoom Optika Water resistance: IP66 Anti-Cut 3-Axis Bracket Dimenzije: 275(W) x 125(H) x 105(D)mm Težina: 1.7Kg	58,10 €
HD-CVI kamere 1,3 MPIX				
48		NC-13FD1	NC-13FD1 1/3" SONY 1.3MP CMOS senzor, 960P/960H, sa IR-CUT, Low Illumination, DNR, antivandal IR Dome kamera Nove IR LED diode: 14µ x 18PCS IR LED diode: € 5 (12µ) x 24PCS (Optional) Domet IR dioda: 20M Optika na ploči 2.8mm/F2.0 Dimenzije: € 89 x 76(H) mm Težina: 450g	40,60 €
49		NC-13FB2	NC-13FB2 1/3" SONY 1.3MP CMOS Senzor, 960P/960H, sa IR-CUT, Low Illumination, DNR, Plastična vodootporna IR kamera IR LED diode: 14µ x 18PCS IR domet: 20M Board optika 2.8mm/F2.0 Stepen zaštite: IP66 Nosač sa 3-ose rotacije i zaštitom od sečenja kabla	40,60 €
50		NC-13FB	NC-13FB bullet HD-CVI kamera 1/3" Aptina CMOS Senzor 1.3MP/720P/With IR-CUT Low Illumination, 3D NR IR LED: € 5X30PCS Domet IR dioda: 25M Board Optika 3.6mm/F2.0 Vodootporna: IP66 Anti-Cut Nosač sa 3-ose rotacije Dimenzije: 142(W) x 68(H) x 66(D)mm Težina: 500g	49,00 €

Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd
Tel:+381 11 3103-999, fax. +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg

CENOVNIK OPREME VIDEO NADZOR 22-09-

R. Br.	Slika	Model	Opis	Cena (EUR)
51		NC-13FB4	NC-13VF4 bullet HD-CVI kamera 1/3" Aptina CMOS Senzor 1.3MP/720P/With IR-CUT Low Illumination, 3D NR IR LED: € 5X48PCS Domet IR dioda: 40M Board Optika 3.6mm/F2.0 Vodootporna: IP66 Anti-Cut Nosač sa 3-ose rotacije Dimenzije: 177(W) x 76(H) x 74(D)mm Težina: 700g	64,40 €
52		LIP40CV130 (LIK41SL)	LIP40CV130 1/3" Aptina CMOS Senzor 1.3MP/720P/With IR-CUT Low Illumination, 3D NR IR LED: € 5X42PCS Domet IR dioda: 40M 2.8-12mm Optika sa ručnim podešavanjem zuma Vodootporna: IP66 Anti-Cut Nosač sa 3-ose rotacije Dimenzije: 260(W) x 112(H) x 85(D)mm Težina: 1.4Kg	75,60 €
53		NC-13VFB (LIP90CV130)	NC-13VFB bullet HD-CVI kamera 1/3" Aptina CMOS Senzor 1.3MP/720P/With IR-CUT Low Illumination, 3D NR IR LED: € 5X72PCS Domet IR dioda: 60M 2.8-12mm Optika sa ručnim podešavanjem zuma Vodootporna: IP66 Anti-Cut Nosač sa 3-ose rotacije Dimenzije: 275(W) x 125(H) x 105(D)mm Težina: 1.7Kg	81,20 €
54		NC-13VFD	NC-13VFD HD-CVI vandal dome kamera "1/3"" Aptina CMOS Senzor 1.3MP/960P/With IR-CUT Low Illumination, WDR, 3D NR, UTC" Antivandal IR Dome kamera IR LED: € 5X36PCS Domet IR dioda: 30M 2.8-12mm Optika sa ručnim podešavanjem zuma Dimenzije: 125(W) x 105.8(H) x 135(D) mm Težina: 800g	61,60 €
55		NC-13VFD2	NC-13VFD2 HD-CVI vandal dome kamera 1/3" Aptina CMOS Senzor 1.3MP/720P/With IR-CUT Low Illumination, 3D NR Antivandal IR Dome kamera IR LED: € 5X36PCS Domet IR dioda: 30M 2.8-12mm Optika sa ručnim podešavanjem zuma Blue, Orange or Black Rubber Ring Dimenzije: € 131 x 93(H) mm Težina: 800g	61,60 €
HD-CVI kamere 2,4 MPIX				
56		NC-24FB20	NC-24FB20 HD-CVI bullet kamera 1/2.9" SONY 2.4MP CMOS Sensor, 1080P, With IR-CUT, Low Illumination, WDR, DNR, UTC IR LED: 42µ x 1PCS IR range: 20M Board Optika 3.6mm/F2.0 Water Resistance: IP66 Dimenzije: 130(W) x 77.5(H) x 80(D)mm Težina: 800g	51,66 €
57		NC-24FB40	NC-24FB40 HD-CVI bullet kamera 1/2.9" SONY 2.4MP CMOS Sensor, 1080P, With IR-CUT, Low Illumination, WDR, DNR, UTC IR LED: 42µ x 2PCS IR rang: 40M CS Optika 6mm, (opciono 3,6mm) /F2.0 Water Resistance:IP66 Dimenzije:291.5(W)x101.5(H)x97.5(D)mm Težina:1.7kg	61,46 €
58		NC-24VFD	NC-24VFD HD-CVI vandal dome kamera 1/2.9" SONY 2.4MP CMOS Sensor, 1080P With IR-CUT, Low Illumination, WDR, DNR, UTC Vandalproof IR Dome Kamera IR LED: € 5 (12µ) x 24PCS IR range: 20M Board Optika 3.6mm/F2.0 Dimenzije: € 89 x 76(H) mm Težina:450g	44,66 €
59		NC-21VFD	NC-21VFD HD-CVI vandal dome kamera PAL 1/2.9 SONY 2.4MP CMOS Sensor 1080P With IR-CUT Low Illumination WDR DNR UTC 2.8-12mm Manual Zoom Lens brilliant white; Vandalproof IR Dome Camera IR LED: € 5 (12µ) x 36PCS IR range: 30M 2.8-12mm Manual Zoom Lens Size: 125(W) x 105.8(H) x 135(D) mm Weight: 800g	55,86 €
60		NC-24FB	NC-24FB HD-Cvi bullet kamera 1/2.9" SONY 2.4MP CMOS Sensor, 1080P, With IR-CUT, Low Illumination, WDR, DNR, UTC IR LED: € 5 (12µ) x 30PCS IR range: 25M Board Optika 3.6mm/F2.0 Water resistance: IP66 Anti-Cut 3-Axis Bracket Dimenzije: 157(W) x 70(H) x 66(D)mm Težina: 650g	46,06 €
61		NC-21VFB	NC-21VFB PAL 1/2.9 SONY 2.4MP CMOS Sensor 1080P With IR-CUT Low Illumination WDR DNR UTC 2.8-12mm Manual Zoom Lens semi-white; NEW IR LED: 14µ x 30PCS IR range: 40M 2.8-12mm Manual Zoom Lens Water resistance: IP66 Anti-Cut 3-Axis Bracket Size: 260(W) x 112(H) x 85(D)mm Weight: 1.4Kg	72,66 €
62		NC-21VFB6	NC-21VFB6 PAL 1/2.9 SONY 2.4MP CMOS Sensor 1080P With IR-CUT Low Illumination WDR DNR UTC 2.8-12mm Manual Zoom Lens semi-white; NEW IR LED: 14µ x 48PCS IR range: 60M 2.8-12mm Manual Zoom Lens Water resistance: IP66 Anti-Cut 3-Axis Bracket Size: 275(W) x 125(H) x 105(D)mm Weight: 1.7Kg	82,60 €

Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd
Tel:+381 11 3103-999, fax. +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg


CENOVNIK OPREME VIDEO NADZOR 22-09-

R. Br.	Slika	Model	Opis	Cena (EUR)
--------	-------	-------	------	------------

NOVO 4 U 1 KAMERE (AHD/CVI/TVI/ANALOGNE) - IZBOR JEDNOG OD 4 UKLJUČIVANJU KAMERE. REZOLUCIJE 1 MEGAPIKSEL (720p) (1000TVL)

			"1/4" AHD/CVI/TVI/CVBS" "1000TVL 1mp 720P" 0.1LUX 1. Support IR CUT/OSD 2. lightning protection 3. 2DNR	
63		NC-10FDP41	1/4" OV 1.0MP CMOS senzor, 720P, sa IR-CUT, DNR, plastična IR Dome kamera IR LED diode: 14µ x 18PCS Domet IR dioda: 20M Optika na ploči 2.8mm/F2.0 Dimenzije: 90.5(W) x 80(H) x 80(D)mm Težina: 300g	29,40 €
64		NC-10FDM41	1/4" OV 1.0MP CMOS senzor, 720P, sa IR-CUT, DNR, , antivandal IR Dome kamera Nove IR LED diode: 14µ x 18PCS IR LED diode: € 5 (12µ) x 24PCS (Optional) Domet IR dioda: 20M Optika na ploči 2.8mm/F2.0 Dimenzije: € 89 x 76(H) mm Težina:450g	35,00 €
65		NC-10FD241	1/4" OV 1.0MP CMOS senzor, 720P, sa IR-CUT, DNR , antivandal IR Dome kamera IR LED diode: 18.5µ x 2PCS Domet IR dioda: 20M Optika na ploči 2.8mm/F2.0 Dimenzije: € 120 x 100(H) mm Težina: 800g	50,40 €
66		NC-10FBP41	1/4" OV 1.0MP CMOS senzor, 720P, sa IR-CUT, DNR , plastična Weatherproof IR kamera IR LED diode: 14µ x 18PCS Domet IR dioda: 20M Board Len 2.8mm/F2.0 stepen zaštite: IP66 Nosač sa 3-ose rotacije i zaštitom od sečenja kabla Dimenzije: 160.8(W) x 62(H) x 62(D)mm Težina: 380g	29,40 €
67		NC-10FBM41	1/4" OV 1.0MP CMOS senzor, 720P, sa IR-CUT, DNR , IR LED diode: 14µ x 20PCS Domet IR dioda: 25M Board Len 3.6mm/F2.0 stepen zaštite: IP66 Nosač sa 3-ose rotacije i zaštitom od sečenja kabla Dimenzije: 155.5(W) x 66(H) x 67(D)mm Težina: 750g	30,80 €
68		NC-10FB741	1/4" OV 1.0MP CMOS senzor, 720P, sa IR-CUT, DNR , IR LED diode: 42µ x 4PCS Domet IR dioda: 60M Optika na ploči 4mm/F2.0 stepen zaštite: IP66 Dimenzije: 194(W) x 91(H) x 82(D)mm Težina: 668g sa nosačem	43,40 €
69		NC-10FB841	1/4" OV 1.0MP CMOS senzor, 720P, sa IR-CUT, DNR , IR LED diode: 42µ x 2PCS Domet IR dioda: 60M Optika na ploči 4mm/F2.5 stepen zaštite: IP66 Dimenzije: 167(W) x 87(H) x 97(D)mm Težina: 1.2kgs sa nosačem	56,00 €
70		NC-10FB941	1/4" OV 1.0MP CMOS senzor, 720P, sa IR-CUT, DNR , IR LED diode: 42µ x 4PCS Domet IR dioda: 90M Optika na ploči 4mm/F2.5 stepen zaštite: IP66 Dimenzije: 205(W) x 88(H) x 120(D)mm Težina: 1.3kgs sa nosačem	62,30 €

NOVO 4 U 1 KAMERE (AHD/CVI/TVI/ANALOGNE) - IZBOR JEDNOG OD 4 SIGNALA PRI UKLJUČIVANJU MEGAPIKSELA (1080p) (2000TVL)





			1. Support IR CUT/OSD 2. lightning protection 3. 2DNR 1/2.8" SONY IMX322 CMOS čip, 0.001 LUX / F1.2 AHD/CVI/TVI/CVBS 2MP/1080P 0.001LUX	
71		NC-10FDP42	1/2.8" SONY IMX322 CMOS senzor, 1080P, sa IR-CUT, DNR, plastična IR Dome kamera IR LED diode: 14µ x 18PCS Domet IR dioda: 20M Optika na ploči 2.8mm/F2.0 Dimenzije: 90.5(W) x 80(H) x 80(D)mm Težina: 300g	40,60 €

Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd
Tel:+381 11 3103-999, fax. +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg

CENOVNIK OPREME VIDEO NADZOR 22-09-

R. Br.	Slika	Model	Opis	Cena (EUR)
72		NC-10FDM42	NC-10FDM42 1/2.8" SONY IMX322 CMOS senzor, 1080P, sa IR-CUT, DNR, antivandal IR Dome kamera Nove IR LED diode: 14μ x 18PCS IR LED diode: € 5 (12μ) x 24PCS (Optional) Domet IR dioda: 20M Optika na ploči 2.8mm/F2.0 Dimenzije: € 89 x 76(H) mm Težina: 450g	46,20 €
73		NC-10FD242	1/2.8" SONY IMX322 CMOS senzor, 1080P, sa IR-CUT, DNR, antivandal IR Dome kamera IR LED diode: 18.5μ x 2PCS Domet IR dioda: 20M Optika na ploči 2.8mm/F2.0 Dimenzije: € 120 x 100(H) mm Težina: 800g	61,60 €
74		NC-10FBP42	1/2.8" SONY IMX322 CMOS senzor, 1080P, sa IR-CUT, DNR, plastična Weatherproof IR kamera IR LED diode: 14μ x 18PCS Domet IR dioda: 20M Board Len 2.8mm/F2.0 stepen zaštite: IP66 Noslač sa 3-ose rotacije i zaštitom od sečenja kabla Dimenzije: 160.8(W) x 62(H) x 62(D)mm Težina: 380g	40,60 €
75		NC-10FBM42	1/2.8" SONY IMX322 CMOS senzor, 1080P, sa IR-CUT, DNR, IR LED diode: 14μ x 20PCS Domet IR dioda: 25M Board Len 3.6mm/F2.0 stepen zaštite: IP66 Noslač sa 3-ose rotacije i zaštitom od sečenja kabla Dimenzije: 155.5(W) x 66(H) x 67(D)mm Težina: 750g	42,00 €
76		NC-10FB742	1/2.8" SONY IMX322 CMOS senzor, 1080P, sa IR-CUT, DNR, IR LED diode: 42μ x 4PCS Domet IR dioda: 60M Optika na ploči 4mm/F2.0 stepen zaštite: IP66 Dimenzije: 194(W) x 91(H) x 82(D)mm Težina: 668g sa noslačem	54,60 €
77		NC-10FB842	1/2.8" SONY IMX322 CMOS senzor, 1080P, sa IR-CUT, DNR, IR LED diode: 42μ x 2PCS Domet IR dioda: 60M Optika na ploči 4mm/F2.5 stepen zaštite: IP66 Dimenzije: 167(W) x 87(H) x 97(D)mm Težina: 1.2kgs sa noslačem	67,20 €
78		NC-10FB942	1/2.8" SONY IMX322 CMOS senzor, 1080P, sa IR-CUT, DNR, IR LED diode: 42μ x 4PCS Domet IR dioda: 90M Optika na ploči 4mm/F2.5 stepen zaštite: IP66 Dimenzije: 205(W) x 88(H) x 120(D)mm Težina: 1.3kgs sa noslačem	73,50 €

NOVO 4 U 1 KAMERE (AHD/CVI/TVI/ANALOGNE) - IZBOR JEDNOG OD 4 SIGNALA PRI UKLJUČIV MEGAPIKSELA (1080p) (2000TVL) 0.0001LUX STARLIGHT

			0.0001 LUX / F1.2 AHD/CVI/TVI/CVBS 2MP/1080P Starlight, 1. Support IR CUT/OSD 2. lightning protection 3. 2DNR	
79		NC-10FDP42S	1/2.8" SONY IMX291 CMOS senzor, 1080P, sa IR-CUT, DNR, plastična IR Dome kamera IR LED diode: 14μ x 18PCS Domet IR dioda: 20M Optika na ploči 2.8mm/F2.0 Dimenzije: 90.5(W) x 80(H) x 80(D)mm Težina: 300g	46,20 €
80		NC-10FDM42S	1/2.8" SONY IMX291 CMOS senzor, 1080P, sa IR-CUT, DNR, antivandal IR Dome kamera Nove IR LED diode: 14μ x 18PCS IR LED diode: € 5 (12μ) x 24PCS (Optional) Domet IR dioda: 20M Optika na ploči 2.8mm/F2.0 Dimenzije: € 89 x 76(H) mm	51,80 €
81		NC-10FD242S	1/2.8" SONY IMX291 CMOS senzor, 1080P, sa IR-CUT, DNR, antivandal IR Dome kamera IR LED diode: 18.5μ x 2PCS Domet IR dioda: 20M Optika na ploči 2.8mm/F2.0 Dimenzije: € 120 x 100(H) mm Težina: 800g	67,20 €
82		NC-10FBP42S	1/2.8" SONY IMX291 CMOS senzor, 1080P, sa IR-CUT, DNR, plastična Weatherproof IR kamera IR LED diode: 14μ x 18PCS Domet IR dioda: 20M Board Len 2.8mm/F2.0 stepen zaštite: IP66 Noslač sa 3-ose rotacije i zaštitom od sečenja kabla Dimenzije: 160.8	46,20 €



Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd
Tel: +381 11 3103-999, fax. +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg

CENOVNIK OPREME VIDEO NADZOR 22-09-

R. Br.	Slika	Model	Opis	Cena (EUR)
83		NC-10FBM42S	1/2.8" SONY IMX291 CMOS senzor, 1080P, sa IR-CUT, DNR , IR LED diode: 14μ x 20PCS Domet IR dioda: 25M Board Len 3.6mm/F2.0 stepen zaštite: IP66 Noslač sa 3-ose rotacije i zaštitom od sečenja kabla Dimenzije: 155.5(W) x 66(H) x 67(D)mm Težina: 750g	47,60 €
84		NC-10FB742S	1/2.8" SONY IMX291 CMOS senzor, 1080P, sa IR-CUT, DNR , IR LED diode: 42μ x 4PCS Domet IR dioda: 60M Optika na ploči 4mm/F2.0 stepen zaštite: IP66 Dimenzije: 194(W) x 91(H) x 82(D)mm Težina: 668g sa noslačem	60,20 €
85		NC-10FB842S	1/2.8" SONY IMX291 CMOS senzor, 1080P, sa IR-CUT, DNR , IR LED diode: 42μ x 2PCS Domet IR dioda: 60M Optika na ploči 4mm/F2.5 stepen zaštite: IP66 Dimenzije: 167(W) x 87(H) x 97(D)mm Težina: 1.2kgs sa noslačem	72,80 €
86		NC-10FB942S	1/2.8" SONY IMX291 CMOS senzor, 1080P, sa IR-CUT, DNR , IR LED diode: 42μ x 4PCS Domet IR dioda: 90M Optika na ploči 4mm/F2.5 stepen zaštite: IP66 Dimenzije: 205(W) x 88(H) x 120(D)mm Težina: 1.3kgs	79,10 €

NOVO 4 U 1 KAMERE (AHD/CVI/TVI/ANALOGNE) - IZBOR JEDNOG OD 4 SIGNALA PRI UKLJUČIV MEGAPIKSELA (1080p) (2000TVL) 0.0001LUX SA VARIFOKALNIM ZUMOM

87		NC-24VFB6	NC-24VFB6 1/3" Panasonic 2.4MP CMOS Sensor, 1080P/960H, With IR-CUT, Low Illumination, WDR, 3DNR, Defog, Sense-up, UTC, OSD IR LED: 42μ x 4PCS IR range: 60M 2.8-12mm Manual Zoom Lens Water resistance: IP66 Anti-Cut 3-Axis Bracket Size: 260(W) x 112(H) x 85(D)mm Weight: 1.4Kg	74,20 €
88		NC-24VFB9	NC-24VFB9 1/3" Panasonic 2.4MP CMOS Sensor, 1080P/960H, With IR-CUT, Low Illumination, WDR, 3DNR, Defog, Sense-up, UTC, OSD, IR LED: 42μ x 6PCS IR range: 90M 2.8-12mm Manual Zoom Lens Water resistance: IP66 Anti-Cut 3-Axis Bracket Size: 275(W)x125(H)x105(D)mm Weight: 1.7Kg	82,60 €

NOVO 4 U 1 KAMERE (AHD/CVI/TVI/ANALOGNE) - IZBOR JEDNOG OD 4 SIGNALA PRI UKLJUČIV MEGAPIKSELA (1080p) (2000TVL) 0.0001LUX SA MOTORIZOVANIM ZUMOM

89		NC-24MZD3	NC-24MZD3 1/2.9" SONY 2.4MP CMOS Sensor, 1080P/960H, With IR-CUT, Low Illumination WDR, 3DNR, Defog, Sense-up, UTC, OSD 2.8-12mm Motor Zoom & Auto Focus Lens, Vandalproof & Weatherproof IR Dome Camera Water resistance: IP66 NEW IR LED: 14μ x 24PCS IR range: 30M 2.8-12mm Motorizovani zum Size: 125(W) x 105.8(H) x 135(D) mm Weight: 800g	65,80 €
90		NC-24MZF6	NC-24MZF6 1/2.9" SONY 2.4MP CMOS Sensor, 1080P/960H, With IR-CUT, Low Illumination WDR, 3DNR, Defog, Sense-up, UTC, OSD 2.8-12mm Motor Zoom & Auto Focus Lens, IR LED: 42μ x 4PCS IR range: 60M 2.8-12mm Motorizovani zum Water resistance: IP66 Anti-Cut 3-Axis Bracket Size: 260(W) x 112(H) x 85(D)mm Weight: 1.4Kg	88,20 €
91		NC-24MZF9	NC-24MZF9 1/2.9" SONY 2.4MP CMOS Sensor, 1080P/960H, With IR-CUT, Low Illumination WDR, 3DNR, Defog, Sense-up, UTC, OSD 2.8-12mm Motor Zoom & Auto Focus Lens, IR LED: 42μ x 6PCS IR range: 90M 2.8-12mm Motorizovani zum Water resistance: IP66 Anti-Cut 3-Axis Bracket Size: 275(W)x125(H)x105(D)mm Weight: 1.7Kg	96,60 €

Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd
Tel:+381 11 3103-999, fax. +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg

CENOVNIK OPREME VIDEO NADZOR 22-09-

R. Br.	Slika	Model	Opis	Cena (EUR)
HD-CVI PTZ kamere 2,4 MPIX				
91		NC-13PT18	NC-13PT18 HD-CVI PTZ kamera 1/2.8" SONY CMOS Sensor 1.3MP/960P/720P Low Illumination, ICR, 2D NR 18X Optical Zoom (f=5mm-90mm) ★ 7" HD-CVI Medium Speed Dome Kamera ★ Weatherproof Outdoor IP66 ★ € 22x8PCS+ € 16x6PCS IR LEDES, IR Range: 120m ★ Pan Range: 0°~360° Continue; Tilt Range: 0°~93° Flip ★ Pan Speed: 60°/sec; Tilt Speed: 45°/sec ★ Preset Points: 220 ★ Guard Tours: 4 Groups ★ Guard Points: Max.16 points ★ RS485, Pelco D/P supported ★ OSD Menu Available ★ Power Adaptor: DC12V/3A ★ Lightning Protection: Transient Voltage 6000V ★ Dimenzije of Package (LxWxH): 32x32x43(mm) ★ Težina: 7Kgs	448,00 €
92		NC-13PT10	NC-13PT10 HD-CVI PTZ kamera 1/3" SONY CMOS Sensor 1.3MP/960P/720P Low Illumination, ICR, 2D NR 10X Optical Zoom (f=5.13mm-46.3mm) ★ 4.5" HD-CVI Mini Medium Speed Dome Kamera ★ Weatherproof Outdoor IP66 ★ € 16x6PCS IR LEDES, IR Range: 60m ★ Pan Range: 0°~360° Continue; Tilt Range: 0°~93° Flip ★ Pan Speed: 45°/sec; Tilt Speed: 30°/sec ★ Preset Points: 220 ★ Guard Tours: 3 Groups ★ Guard Points: Max.16 points ★ RS485, Pelco D/P supported ★ OSD Menu Available ★ Power Adaptor: DC12V/3A ★ Lightning Protection: Transient Voltage 6000V ★ Dimenzije of Package (LxWxH): 29.5x28x17(cm) ★ Težina: 3.4Kgs	308,00 €
NOVO KAMERE 1200TVL				
93		NORA N-1200VFD	N-1200VFD PAL 1/3 CMOS Sensor 1.3MP 960H/TVI 1200TVL Low Illumination IR-CUT DNR Board Lens 3.6mm brilliant white Vandalproof IR Dome Camera IR LED: € 5 (12µ) x 24PCS IR range: 20M Board Lens 3.6mm/F2.0 Size: € 89 x 76(H) mm, Weight:450g 1/3" CMOS Sensor 1.3MP, 960H/TVI, 1200TVL, Low Illumination, IR-CUT, DNR	32,20 €
94	 NOVO 1200 TVL	LIZM40SFS (LIP40SHE)	LIZM40SFS "1/3"" SONY 1.4MP CMOS Senzor, 720P, 1200TVL, Low Illumination IR-CUT, DNR" IR LED: € 5X42PCS Domet IR dioda: 40M 2.8-12mm Optika sa ručnim podešavanjem zuma (2M Pixels) Vodootporna: IP66 Anti-Cut Nosač sa 3-ose rotacije DC12V Dimenzije: 290(W) x 92(H) x 80(D)mm Težina: 1.85KG	80,85 €
95		N-1200VFB	N-1200VFB Bullet kamera 1200TVL 1/3" CMOS Sensor 1.3MP, 960H/TVI, 1200TVL, Low Illumination, IR-CUT, DNR IR LED: € 5X42PCS IR range: 40M 2.8-12mm Manual Zoom Lens (2M Pixels) Water resistance: IP66, Anti-Cut 3-Axis Bracket DC12V, Size: 275(W) x 91(H) x 80(D)mm Weight: 1.4KG	53,20 €
96	 NOVO 1200 TVL	LIRDVSFS (LVDPBSL)	LIRDVSFS "1/3"" SONY 1.4MP CMOS Senzor, 720P, 1200TVL, Low Illumination IR-CUT, DNR" Antivandal IR Dome kamera IR LED: € 5X36PCS Domet IR dioda: 30M 2.8-12mm Optika sa ručnim podešavanjem zuma (2M Pixels) Dimenzije: 125(W) x 105.8(H) x 135(D) mm Težina: 800g	54,60 €
97	 NOVO 1200 TVL	LIP90SFS (LIED90SHE)	LIP90SFS "1/3"" SONY 1.4MP CMOS Senzor, 720P, 1200TVL, Low Illumination IR-CUT, DNR" IR LED: € 5X72PCS Domet IR dioda: 60M 2.8-12mm Optika sa ručnim podešavanjem zuma (2M Pixels) Vodootporna: IP66 Anti-Cut Nosač sa 3-ose rotacije Dimenzije: 275(W) x 125(H) x 105(D)mm Težina: 1.7Kg	81,20 €
98		LIRDSFS (LIRDSSHE)	LIRDSFS 1/3" SONY 1.4MP CMOS Senzor, 720P, 1200TVL, Low Illumination IR-CUT, DNR Antivandal IR Dome kamera IR LED: € 5X24PCS Domet IR dioda: 20M Board Optika 3.6mm/F2.0 Dimenzije: € 89 x 76(H) mm Težina:450g	39,20 €

Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd
Tel: +381 11 3103-999, fax. +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg









CENOVNIK OPREME VIDEO NADZOR 22-09-

R. Br.	Slika	Model	Opis	Cena (EUR)
99		LICE24NSFS (LCDNT20SHE)	1/3" SONY 1.4MP CMOS Senzor, 720P, 1200TVL, Low Illumination IR-CUT, DNR IR LED: € 5X24PCS Domet IR dioda: 20M Board Optika 3.6mm/F2.0 Vodootporna: IP66 Anti-Cut Nosač sa 3-ose rotacije Dimenzije: 86(W) x 60(H) x 55(D)mm Težina: 400g	52,36 €
KAMERE 1000TVL				
100		LIZM40SFP (LIA100SL)	LIZM40SFP "1/3" SONY 1.4MP CMOS Senzor, 720P, 1000TVL, Low Illumination OSD, IR-CUT, 3D NR, WDR, digitalni Zoom, UTC Optional IR LED: € 5X42PCS Domet IR dioda: 40M 2.8-12mm Optika sa ručnim podešavanjem zuma (2M Pixels) Vodootporna: IP66Anti-Cut Nosač sa 3-ose rotacije Dimenzije: 290(W) x 92(H) x 80(D)mm težina: 1.85KG	83,79 €
101		LIRDCSFP	LIRDCSFP 1/3" SONY 1.3 Megapikselni Senzor 1/3" SONY CMOS (IMX138LQJ-C)+FH8520, 720P, 1000TVL, Low Illumination, ugrađen OSD meni, IR-CUT, 3D NR, digitalni zum, UTC ANTIVANDAL IR Dome Kamera Infracrvene diode: € 5X36komada domet IC dioda: 30M 2.8-12mm ručno podešiva optika (2M Pixels) dimenzije: € 131 x 93(H) mm Težina: 800g. BOJE: SIVA ILI BELA	58,74 €
102		LIRDVSFP (LIA200SL)	LIRDVSFP 1/3" SONY 1.4MP CMOS Senzor, 720P, 1000TVL, Low Illumination OSD, IR-CUT, 3D NR, WDR, digitalni Zoom, UTC Optional Antivandal IR Dome kamera IR LED: € 5X36PCS Domet IR dioda: 30M 2.8-12mm Optika sa ručnim podešavanjem zuma (2M Pixels) Dimenzije: 125(W) x 105.8(H) x 135(D) mm težina: 800g	62,94 €
103		LIRDNSFP (LIRDNSHE)	LIRDNSFP 1/3" SONY 1.3 Megapikselni Senzor, 720P, 1000TVL, Low Illumination, OSD, IR - CUT, 3D NR, digitalni Zum, UTC Antivandal IR Dome Kamera IR LED: € 5X24PCS IR domet: 20M Board Optika 3.6mm/F2.0 Veličina: € 94 x 69(H) mm Težina: 450g	42,70 €
104		LIP90SFP	LIP90SFP 1/3" SONY 1.3 Megapikselni Senzor, 720P, 1000TVL, Low Illumination, OSD, IR - CUT, 3D NR, digitalni Zum, UTC IR LED: € 5X72PCS IR domet: 60M 2.8 - 12mm Manual Zoom Optika (2M Pixels) Vodootporna: IP66 3 - Axis cable built - in bracket Veličina: 275(W) x 125(H) x 105(D)mm Težina: 1.7Kg	88,63 €
105		LBH24SFP (LICG24SHE)	LBH24SFP 1/3" SONY 1.3 Megapikselni Senzor, 720P, 1000TVL, Low Illumination, OSD, IR - CUT, 3D NR, digitalni Zum, UTC IR LED: € 5X24PCS IR domet: 20M Board Optika 3.6mm/F2.0 Vodootporna: IP66 3 - Axis cable built - in bracket Veličina: 148(W) x 65(H) x 63(D)mm Težina: 500g	43,40 €
106		LICE24NSFP	LICE24NSFP 1/3" SONY 1.3 Megapikselni Senzor, 720P, 1000TVL, Low Illumination, OSD, IR - CUT, 3D NR, digitalni Zum, UTC IR LED: € 5X24PCS IR domet: 20M Board Optika 3.6mm/F2.0 Vodootporna: IP66 3 - Axis cable built - in bracket Veličina: 86(W) x 60(H) x 55(D)mm Težina: 400g	43,40 €
KAMERE 800TVL				
107		N-800FD	N-800FD dome vandal kamera N-800FD 1/3" HDIS 960H, 800TVL, With IR-CUT, UTC ANTIVANDAL IR Dome Kamera Infracrvene diode: € 5X24komada domet IC dioda: 20M Optika na ploči 3.6mm/F2.0 dimenzije: € 94 x 69(H) mm Težina: 450g	26,46 €
108		LICE24NSM (LIED40SHE)	LICE24NSM 1/3" HDIS 960H, 800TVL, With IR-CUT, UTC Infracrvene diode: € 5X24komada domet IC dioda: 20M Optika na ploči 3.6mm/F2.0 Vodootporna: IP66 3 ose prolaz kabla kroz nosač dimenzije: 86(W) x 60(H) x 55(D)mm Težina: 400g	29,40 €
KAMERE 700TVL				
109		LIA40ESHE	LIA40ESHE (SIVA BOJA) kolor 1/3" SONY 700TVL,960H, Low Illumination, ATR, ugrađen OSD meni, DNR Sony 672/673 + Sony Effio - e Infracrvene diode: € 5X42komada domet IC dioda: 40M 2.8 - 12mm ručno podešiva optika (2M Pixels) Vodootporna: IP66 DC12V DIMENZIJE: 200(Š)x171(V)x83(D)mm TEŽINA: 1.4Kg,	52,43 €
110		LIRDVSHE (LCDSSHE)	Dome anti-vandal IR kamera 1/3" SONY CCD, 960H, 700TVL, Low Illumination DWDR, OSD, DNR, Smart-IR, UTC Optional Effio-E IR LED: € 5X36PCS Domet IR dioda: 30M 2.8-12mm Optika sa ručnim podešavanjem zuma (2M Pixels) Dimenzije: 125(W) x 105.8(H) x 135(D) mm težina: 800g	54,53 €



Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd
Tel: +381 11 3103-999, fax. +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg

CENOVNIK OPREME VIDEO NADZOR 22-09-

R. Br.	Slika	Model	Opis	Cena (EUR)
111		LIRDNSHE	Kamera LIRDNSHE 1/3" SONY CCD, 960H, 700TVL, Low Illumination DWDR, OSD, DNR Effio-E ANTIVANDAL IR Dome Kamera Infracrvene diode: € 5X24komada domet IC dioda: 20M Optika na ploči 3.6mm/F2.0 dimenzije: € 94 x 69(H) mm Težina: 450g	38,96 €
112		LIP90SHE	LIP90SHE Color 1/3" SONY, 960H, 700TVL, Low Illumination, DWDR, ugrađen OSD meni, DNR, UTC Effio-E Infracrvene diode: € 5X72komada domet IC dioda: 60M 2.8-12mm ručno podešiva optika (2M Pixels) Vodootporna: IP66 3 ose prolaz kabla kroz nosač Dimenzije: 275(W) x 125(H) x 105(D)mm Težina: 1.7Kg	76,44 €
113		LICE24NSHE	LICE24NSHE Color 1/3" SONY 700TVL, Low Illumination, ATR, ugrađen OSD meni, DNR Sony 672/673 + Sony Effio - e Infracrvene diode: € 5X24komada domet IC dioda: 20M Optika na ploči 3.6mm/F2.0 Vodootporna: IP663 - ose kabl u nosaču DIMENZIJE: 86(Š) x60(V) x55(D)mm TEŽINA: 400g	37,80 €
114		LIRDPHNB (LIRDSSH)	LIRDPHNB Color 1/3" SHARP, 960H, 700TVL, Low Illumination Plastic IR Dome Kamera Infracrvene diode: € 5X24komada domet IC dioda: 20M Optika na ploči 3.6mm/F2.0 Dimenzije: € 94 x 69(H) mm Težina: 300g	31,57 €
KAMERE 600TVL				
115		LIRDNHBB	LIRDNHBB Color 1/3" SHARP 600TVL, Low Illumination Sharp RJ2355/RJ2365 + Sharp 36B15 ANTIVANDAL IR Dome Kamera Infracrvene diode: € 5X24komada domet IC dioda: 20M Optika na ploči 3.6mm/F2.0 DIMENZIJE: € 94 x 69(H) mm TEŽINA: 400g	33,11 €
116		LICE24NHBB (LICG24SHE)	LICE24NHBB Color 1/3" SHARP 600TVL, Low Illumination Sharp RJ2355/RJ2365 + Sharp 36B15 Infracrvene diode: € 5X24komada domet IC dioda: 20M Optika na ploči 3.6mm/F2.0 Vodootporna: IP66 3 - ose kabl u nosaču DIMENZIJE: 86(Š) x60(V) x55(D)mm Težina: 400g	26,60 €
117		LIRDPHBB	LIRDPHBB Color 1/3" SHARP 600TVL, Low Illumination Plastic IR Dome Kamera Infracrvene diode: € 5X24komada domet IC dioda: 20M Optika na ploči 3.6mm/F2.0 Dimenzije: € 94 x 69(H) mm Težina: 300g	26,60 €
118		LMCM25SHD (LICG30SHE)	1/3" SONY CCD 650TVL, Low Illumination, DWDR, OSD, DNR, 3.7mm Taper Pinhole Lens Dimenzije: 25(W) x 10(H) x 25(D)mm Težina: 150g	44,66 €

Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd
Tel: +381 11 3103-999, fax. +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg

CENOVNIK OPREME VIDEO NADZOR 22-09-

R. Br.	Slika	Model	Opis	Cena (EUR)
IP KAMERE 4 MEGAPIKSELA				
119		NNC-40VFB	NNC-40VFB IP bullet kamera 4 megapiksela 1/3" OV 4MP High-resolution CMOS Sensor OV4689 + Hi3516D HISILICON Hi3516D, WDR; With IR-CUT; Built-in POE Main Stream: 4MP@20fps, 3MP/1080P@30fps; 3MP HD Lens IR LED: € 5X72PCS IR range: 60M 2.8-12mm Manual Zoom Lens Water resistance: IP66 Anti-Cut 3-Axis Bracket Size: 275(W)x125(H)x105(D)mm Weight: 1.7Kg	142,80 €
120		NNC-40VFD	NNC-40VFD IP vandal dome kamera Vandalproof IR Dome Camera IR LED: € 5X36PCS IR range: 30M 2.8-12mm Manual Zoom Lens Size:125(W)x105.8(H)x135(D)mm Weight: 800g 1/3 OV 4MP High-resolution CMOS Sensor HISILICON Hi3516D WDR 4MP 3MP/1080P 3MP With IR-CUT 2.8-12mm Manual Zoom Lens brilliant white With External POE	142,80 €
121		NNC-32VFB	NNC-32VFB 1/2.8 SONY 3.2MP Starvis Back-illuminated CMOS Sensor Ambarella S2L Low-stream WDR 3MP/1080P/720P 3MP HD With IR-CUT 2.8-12mm Manual Zoom Lens semi-white With Built-in POE IR LED: € 5X72PCS IR range: 60M 2.8-12mm Manual Zoom Lens Water resistance: IP66 Anti-Cut 3-Axis Bracket Size: 275(W)x125(H)x105(D)mm Weight: 1.7Kg	151,20 €
IP KAMERE 3 MEGAPIKSELA				
122	 	LVWDC20T200 (LVDPBSL)	LVWDC20T200 * IMX222 + DM368 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Optika, with IR-CUT *3 - Axis Antivandal & Waterproof Dome Kamera Vodooporna: IP66 IR LED: € 5X21PCS IR domet: 20M 2.8 - 12mm Manual Zoom Optika Veličina: φ151x108(H)mm Težina: 1.2KG POE ili 12VDC napajanje (izbor pri kupovini)	166,60 €
123		LIZM40A200 (LIXT40SL)	LIZM40A200 FULL HD IP kamera IR LED: € 5X42PCS Domet IR dioda: 40M 2.8-12mm Optika sa ručnim podešavanjem zuma Vodooporna: IP66 Anti-Cut Nosač sa 3-ose rotacije Dimenzije: 290(W) x 92(H) x 80(D)mm težina: 1.85KG LIZM40A200 IMX222 + A5S66 1/2.8" SONY 2.4MP High-resolution CMOS Sensor Ambarella A5S66, Low-stream, WDR; Built-in POE Main Stream: 1080P/720P@30fps; 3MP HD Lens, With IR-CUT	152,60 €
124		LIRDNTA200	LIRDNTA200 FULL HD IP Antivandal IR Dome kamera IR LED: € 5X36PCS Domet IR dioda: 30M 2.8-12mm Optika sa ručnim podešavanjem zuma Blue/Orange/Black Rubber Ring Dimenzije: € 131 x 93(H) mm težina: 800g LIRDNTA200 IMX222 + A5S66 1/2.8" SONY 2.4MP High-resolution CMOS Sensor Ambarella A5S66, Low-stream, WDR; External POE Main Stream: 1080P/720P@30fps; 3MP HD Lens, With IR-CUT	151,20 €
IP KAMERE 2 MEGAPIKSELA				
125	 	LIRDNS130	LIRDNS130 *LIRDNS130 IMX138 + Hi3518C 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Optika, with IR-CUT External POE *Antivandal IR Dome Kamera IR LED: € 5X24PCS IR domet: 20M Board Optika 3.6mm/F2.0 Veličina: € 94 x 69(H) mm Težina: 450g	54,60 €



Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd
Tel: +381 11 3103-999, fax. +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg

CENOVNIK OPREME VIDEO NADZOR 22-09-

R. Br.	Slika	Model	Opis	Cena (EUR)
126		LBH24S130 (LCDMIR24SL)	LBH24S130 "LBH24S130 IMX138 + Hi3518C 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Optika, with IR-CUT Built-in/External POE "IR LED: € 5X24PCS IR domet: 20M Board Optika 3.6mm/F2.0 Vodootporna: IP66 3 - Axis cable built - in bracket Veličina: 148(W) x 65(H) x 63(D)mm Težina: 500g	54,60 €
IP PTZ KAMERE				
127		NNC-2PT22	NNC-2PT22 IP PTZ kamera 1/2.7" OmniVision Low Illumination 2MP CMOS Sensor, Hisilicon Hi3516C Main Stream: 1080P@30fps; With IR-CUT 22X Optical Zoom (f=3.9mm-85.5mm) ★ 7" HD-IP High Speed Dome Kamera ★ Weatherproof Outdoor IP66 ★ € 22x8PCS+ € 16x6PCS IR LED, IR Range: 120m ★ Pan Range: 0°-360° Continue; Tilt Range: 0°-90° Flip ★ Pan Speed: 200°/sec; Tilt Speed: 100°/sec ★ Preset Points: 220 ★ Guard Tours: 3 Groups ★ Guard Points: Max. 16 points ★ TCP/IP, HTTP, FTP, RTSP Support ★ P2P Support ★ Power Adaptor: DC12V/4A ★ Lightning Protection: Transient Voltage 6000V ★ Dimenzije of Package (LxWxH): 32x32x43(cm) ★ Težina: 7Kgs	474,32 €
INFRACRVENI LED REFLEKTORI				
128		LEDI 80	114komada €8-14µ Infracrvene diode Available IR distance: 80m dimenzije: 150(H)X120(L)X88(W) mm težina: 1.8kg Weatherproof of IR Illuminator	49,28 €
129		LEDI 130	198komada €8-14µ Infracrvene diode Available IR distance: 130m dimenzije: 200(H)X143(L)X88(W) mm težina: 2.0kg Weatherproof of IR Illuminator	69,30 €
UTC kontroleri				
130		UTC Controller STC12	UTC Controller STC12 UTC Controller Through Coaxial Cable Dimenzije: 112(H) x 48(L) x 10(W) težina: 100g	7,70 €
PTZ kamere				
131		LPTD10XCG	LPTD10XCG 1/3" SONY Super HAD II CCD+Effio - E, 10X(f=3.8~38mm), Color 650TVL Mini Slow Speed Dome kamera Antivandal & Indoor IR Working Distance: 40M Pan Range: 360° Continuous rotation Tilt range: 0°-90° Flip/Auto flip 180° Pan Speed: Max 50°/sec Preset: 256, 4 pattern scans, 8 cruise line RS485, Pelco D/P supported Built - in full - screen OSD	278,28 €
132		PT6A022	PT6A022 "6" Medium Speed Dome kamera Weatherproof Outdoor IP66 € 20x6PCS+ € 16x5PCS IR LED, Domet IR dioda: 100m Pan Range: 0°-360° Continue; Tilt Range: 0°-94° Flip Pan Speed: 60°/sec; Tilt Speed: 30°/sec Preset Points: 220 Guard Tours: 3 Groups Guard Points: Max.16 points RS485, Pelco D/P supported Power Adaptor: DC12V/4A Lightning Protection: Transient Voltage 3000V Dimenzije of Package (LxWxH): 28x28x42(cm) težina: 3.8Kgs* PT6A022 "1/3" Super HAD II SONY CCD, Effio 22X Optical Zoom (f=3.9mm-85.5mm) Color 650TVL, Black 700TVL	338,80 €

Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd
Tel: +381 11 3103-999, fax. +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg

CENOVNIK OPREME VIDEO NADZOR 22-09-

R. Br.	Slika	Model	Opis	Cena (EUR)
KOAKSIJALNI KABLOVI RG-59				
133		RG59 100m	RG-59 koaksijalni kabl 75 Ohm na buntu 100m	0,16 €
134		RG-59 305m	RG-59 koaksijalni kabl 75 Ohm na drvenom koturu 305m	0,16 €
135		RG-59+2x0,5 100m	RG-59 koaksijalni kabl 75 Ohm sa napojnim kablom 2x0.5mm2 na buntu 100m CRNA BOJA. RG59: 22AWG 0.64mm bare copper, 3.71mm Foam PE insulation, Al Foil, 90% mesh (16x7x0.12mm CCA wires) braiding, 6.10mm PVC Jacket Power Wires: 2cores 0.50mm ² copper, 1.8mm PVC Insulation (red/Black), 5.0mm PVC Jacket	0,26 €
136		RG-59+2x0,5 305m	RG-59 koaksijalni kabl 75 Ohm sa napojnim kablom 2x0.5mm2 na drvenom koturu 305m. CRNA BOJA. RG59: 22AWG 0.64mm bare copper, 3.71mm Foam PE insulation, Al Foil, 90% mesh (16x7x0.12mm CCA wires) braiding, 6.10mm PVC Jacket Power Wires: 2cores 0.50mm ² copper, 1.8mm PVC Insulation (red/Black), 5.0mm PVC Jacket	0,26 €
137		RG-59+2x0,75 100m	RG-59 koaksijalni kabl 75 Ohm sa napojnim kablom 2x0.75mm2 na buntu 100m. CRNA BOJA. RG59: 22AWG 0.64mm bare copper, 3.71mm Foam PE insulation, Al Foil, 90% mesh (16x7x0.12mm CCA wires) braiding, 6.10mm PVC Jacket Power Wires: 2cores (0.75 square mm) copper, 2.0mm PVC Insulation (red/Black), 5.0mm PVC Jacket	0,33 €
138		RG-59+2x0,75 305m	RG-59 koaksijalni kabl 75 Ohm sa napojnim kablom 2x0.75mm2 na drvenom koturu 305m. CRNA BOJA. RG59: 22AWG 0.64mm bare copper, 3.71mm Foam PE insulation, Al Foil, 90% mesh (16x7x0.12mm CCA wires) braiding, 6.10mm PVC Jacket Power Wires: 2cores (0.75 square mm) copper, 2.0mm PVC Insulation (red/Black), 5.0mm PVC Jacket	0,33 €
139		RG-59 + 2x0,75 + sajla 305m	RG-59 koaksijalni kabl 75 Ohm sa napojnim kablom 2x0.75mm2 i sajlom na drvenom koturu 305m	0,40 €
KOAKSIJALNI KABLOVI RG-6				
140		RG-6 CCS 100m	RG-6 koaksijalni kabl na buntu 100m	0,16 €
141		RG-6 CCS 305m	RG-6 koaksijalni kabl na drvenom koturu 305m	0,16 €
ALARMNI KABLOVI				
142		4x0.22 TCCA	4x0,22 alarmni kabl na koturu 100m TCCA. BELA BOJA	0,12 €
143		6x0.22 TCCA	6x0,22 alarmni kabl na koturu 100m TCCA. BELA BOJA	0,15 €
144		6x0.22 bakar	6x0,22 alarmni kabl na koturu 100m bakar. BELA BOJA	0,26 €
145		8x0.22 TCCA	8x0,22 alarmni kabl na koturu 100m TCCA. BELA BOJA	0,20 €
MREŽNI KABLOVI				
146		UTP CAT 5e CCA 305m	UTP kabl CAT 5e CCA u kutiji 305m PUN PRESEK CAT5e U/UTP: 4x2x24AWG 0.50mm CCA, PE insulation, ripcord, 5.10mm PVC Jacket	0,10 €
147		FTP eksterni CAT 5e CCA	FTP eksterni kabl PUN PRESEK sa sajlom (samonošeci) CAT 5e CCA na koturu CAT5e F/UTP-M: 4x2x24AWG 0.5mm CCA, PE insulation, Aluminum Foil, ripcord, CCA drain wire, 5.70mm PVC Jacket, 1.16mm steel messenger	0,30 €
148		UTP CAT 5e bakar 305m	UTP kabl CAT 5e bakar u kutiji 305m PUN PRESEK	0,23 €
149		UTP CAT 6 CCA 305m	UTP kabl CAT 6 CCA u kutiji 305m PUN PRESEK, CAT6 U/UTP: 4x2x23AWG 0.56mm CCA, PE insulation, cross, ripcord, 6.20mm PVC Jacket	0,18 €
150		UTP CAT 6 bakar 305m	UTP kabl CAT 6 bakar u kutiji 305m PUN PRESEK	0,44 €







Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd
Tel: +381 11 3103-999, fax: +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg

CENOVNIK OPREME VIDEO NADZOR 22-09-











R. Br.	Slika	Model	Opis	Cena (EUR)
KONEKTORI				
151		BNC muški krimp za RG-59	BNC muški krimp konektor za RG-59 kabl	0,21 €
152			F konektor za RG59 kabl. Pakovanje 100 kom.	0,12 €
153			F konektor za RG6 kabl. Pakovanje 100 kom.	0,13 €
154			F nastavak Ženski - Ženski Pakovanje 100 kom	0,21 €
155			BNC konektor muški - F ženski. Pakovanje 100 kom.	0,48 €
156			BNC konektor muški sa šrafo. Pakovanje 100 kom.	0,25 €
157			BNC konektor muški na lemljenje. Pakovanje 100 kom.	0,25 €
158			Profesionalni PPC F konektor za RG59 kabl. Pakovanje 50 kom.	0,40 €
159			Profesionalni PPC F konektor za RG6 kabl. Pakovanje 50 kom.	0,38 €
160			Profesionalni PPC F konektor za RG6 kabl. Pakovanje 50 kom.	2,58 €
161		RJ-45 konektor za CAT5e UTP	RJ-45 konektor kat. 5E - 8-pinski	0,07 €
162		RJ-45 konektor za CAT6 UTP	RJ-45 konektor kat. 6 - 8-pinski	0,14 €
NAPAJANJA				
163		1A	12W/1A/12V DC	4,27 €
164		1AA	12W/1A/12V DC	5,10 €
165		2A	24W/2A/12V DC	5,94 €
166		3A	36W/3A/12V DC	9,51 €
167		5A	60W/5A/12V DC	12,73 €
168		6A	72W/6A/12V DC	14,67 €
169		5A/8CH	5A- stabilisani ispravljač 220Vac/12Vdc M-INOX kutija, reglete za priključivanje 8 kamera, osigurači	35,70 €
170		10A/9CH	120W/10A/12V DC	56,98 €
171		10A/16CH	10A- stabilisani ispravljač 220Vac/12Vdc - čoper M-INOX kutija, reglete za priključivanje 16 kamera, osigurači	51,66 €
172		15A/16CH	180W/15A/12V DC	66,15 €
173		DC-K	1 DC utikač	0,41 €
174		DC-U	1 DC konektor	0,70 €
175		4DC	1 DC utičnica - 4 DC utikača	1,71 €
176		8DC	1 DC utičnica - 8 DC utikača	3,39 €
177		70VA	24 V AC / 70 VA trafo	24,70 €
HARD DISKOVI ZA VIDEO NADZOR				
178		WD5000AAKX	500 GB, SATA II / 16 MB cache, model WD5000AAKX-001CA0	68,60 €

Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd
Tel: +381 11 3103-999, fax. +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg








CENOVNIK OPREME VIDEO NADZOR 22-09-

R. Br.	Slika	Model	Opis	Cena (EUR)
179		WD10EARX	2 TB, SATA II / 64 MB cache, model WD10EARX-00N0YB0 (DO ISTEKA ZALIHA)	112,00 €
180		WD40EZR	4 TB, SATA II / 64 MB cache, model WD40EZR (DO ISTEKA ZALIHA)	196,00 €
181		WD10PURX	Western Digital, 1TB Purple, IntelliPower, SATA III, 64MB	82,04 €
182		WD20PURX	Western Digital, 2TB Purple, IntelliPower, SATA III, 64MB	115,50 €
183		WD30PURX	Western Digital, 3TB Purple, IntelliPower, SATA III, 64MB	155,40 €
184		WD40PURX	Western Digital, 4TB Purple, IntelliPower, SATA III, 64MB	222,60 €

DODATNA OPREMA

185			Audio modul sa izvedenim konektorima. Napajanje 12 V DC	3,39 €
186			Audio modul plastični sa trimrom. Napajanje 12 V DC	5,15 €
187			Audio modul metalni sa trimrom. Napajanje 12 V DC	8,53 €
188			Pasivni jednodokanalni predajnik za prenos video signala, maksimalne dužine do 400 m.	5,15 €
189			Pasivni jednodokanalni predajnik za prenos video signala sa kablom, maksimalne dužine do 400 m.	5,15 €
190			HDCVI video balun (transformator impedanse) za parični kabl Max razdaljina 720P: 400M (max), 1080P: 250M (max) Tip kabla UTP CAT 5E/6 (R < 10Ω/100M) Dolaze u paru: prijemnik+predajnik	7,70 €
191			Aktivni jednodokanalni predajnik za prenos video signala, maksimalni domet 2400 m. Napajanje 12 V DC	20,37 €
192			Aktivni jednodokanalni prijemnik za prenos video signala, maksimalni domet 2400 m. Napajanje 12 V DC	20,37 €
193			A/V modulator CH1 – CH99, PLL, 70dBuV, LED display, napajanje, UF-243	20,86 €
194			A/V modulator CH1 – CH99, PLL, 90dBuV, LED display, napajanje, UF-2432	27,86 €

KUĆIŠTA I NOSAČI

195			Kućište za spoljnu montažu sa grejačem i ventilatorom, nadstrešnica, termozaštićeno, 260x100x75mm, 230Vac, bež boja, bočno otvaranje. Bez nosača.	29,41 €
196			Metalni nosač kućišta kanal za prolaz kablova, dostupni u bež i silver boji	9,80 €
197			Nosač kamere - plastični	2,94 €
198			Nosač, plastični, zidni, ugaoni, za dome kućišta	5,46 €
199			Nosač vandal dome kućišta	10,36 €
200			Spoljno kućište, sa grejačem i termostatom 410mm, dostupni u bež i silver boji, verzije na 12V ili 220V	19,60 €
201			Spoljno kućište, sa grejačem i termostatom, bočno otvaranje 375mm, dostupni u bež i silver boji, verzije na 12V ili 220V	25,06 €
202			Spoljno kućište, sa grejačem, termostatom i ventilatorom, bočno otvaranje	32,06 €
203			Kućište za spoljnu montažu sa grejačem i ventilatorom, nadstrešnica, termozaštićeno, 458x122.3x140.6 mm, 230Vac, bež boja. Radna temperatura -40°C ~ -70°C. IP66 Napajanje 220 V	106,96 €
204			Aluminijumski nosač u boji kućišta. Dimenzije: 304x71x100 mm	16,03 €